

Precision manufacturing delivers consistent rewards.


Strict quality control is the reason that all Nordson precision-manufactured nozzles, including the Saturn series, provide consistent performance.

Nordson nozzle inserts are manufactured and controlled to strict tolerances for inside diameter (orifice) and length (engagement) to maximize your control over adhesive deposition. Lack of precise control over these important factors can result in widely fluctuating adhesive deposition rates that waste adhesive or cause product rejects.

Bead placement accuracy helps reduce product rejects.

Inconsistent bead placement is typical if nozzle specifications are not strictly controlled. Misplaced beads can cause pop-opens, poor product appearance or adhesive buildup on the line that can cause product jams.

Nordson precision nozzles are manufactured to consistently place adhesive beads at a tightly controlled distance of less than $\pm 4^\circ$ from the centerline. In Nordson nozzle conformance testing, our accuracy is normally within 1 to 2° . Other nozzles on the market can exceed this differential by as much as 300%. The further the bead placement drifts from the centerline, the more likely your bond integrity will be jeopardized, resulting in more product rejects.




The bead placement of typical nozzles can vary $\pm 12^\circ$ from desired centerline. Nordson precision nozzles accurately place the bead within $\pm 4^\circ$ from centerline, improving your finished product and reducing adhesive costs.

Flow accuracy and consistency increase application control and reduce adhesive usage.

Strict tolerance control of nozzle dimensions provides accurate, consistent adhesive flow rates. Consistent flow allows you to optimize adhesive patterns for long-term adhesive savings without risking bond quality.

Wide variation in adhesive flow rates between nozzles of the same size is very costly. Variation from the average flow rate between Nordson nozzles of the same size is minimal; about 2 lbs/hr. (0.91 kg/hr.) Some non-genuine Nordson nozzles purported to be the same as Nordson nozzles show undesirable variations from their own average flow rates by as much as 4 lbs/hr. (1.81 kg/hr.).



Inconsistent adhesive flow can be costly. A bead doubled from $1/16''$ to $1/8''$ (1.58 to 3.175 mm) consumes four times more adhesive.

** Beads not shown to actual size.*

What is the cost of inconsistent adhesive nozzle flow to your production? You can experience a very small bead size that can lead to pop-opens or, as typically happens, you will increase your adhesive output to compensate for the lowest volume nozzle on the line. How much additional adhesive could you potentially use? For a typical cartoning line applying 8 one-inch (25.4 mm) beads/carton at 140 cartons/minute, you can consume an additional 90 pounds (41 kg) of glue during one, two-shift day if your bead size doubles from $1/16''$ to $1/8''$ (1.58 to 3.175 mm). Multiply that 90 pounds (41 kg) by your number of production lines and by 200 or more days per year. The annual increased adhesive amount is astounding.

Controlled nozzle manufacturing keeps lines cleaner and running longer.

Since engagement can be used to control adhesive velocity, strict quality control of this dimension permits up-firing and through-rail applications with accurate bead placement and reduced back-splash.

Poorly machined (competitive) nozzles contain imperfections that can create bead problems. Nordson's precision manufacturing processes produce a clean, well-defined tip, enabling precise extrusions that keep lines running smoothly.

Nordson nozzles optimize system performance, simplify replacement and minimize downtime.



Single- and dual-orifice Saturn right-angle nozzles

Nordson Saturn precision nozzles use color-coded rings to visually identify orifice and engagement or orifice and angle. Color-coding allows you to select the correct replacement nozzle every time. Using the right nozzles provides consistency and helps you maintain product quality and smooth line operation while eliminating downtime caused by incorrect or inferior nozzles.

Why are nozzle dimensions so important?

Adhesive bond strength depends on consistent bead size and bead placement. A bead that is too small or misplaced can result in bond failure, while too large a bead can lead to adhesive waste and poor cutoff.

The proper combination of nozzle orifice diameter and engagement length gives you controlled flow for consistent bead size and improved cutoff. For right-angle nozzles, the tip angle is critical for proper bead placement.

Genuine Nordson precision nozzles deliver superior control of adhesive placement and bead width, and provide the most consistent patterns available today.

Nozzles are available in single-orifice, multi-orifice, right-angle and specialty designs.

Saturn nozzles feature easy-to-identify, color-coded rings to simplify nozzle replacement and trouble-shooting.

Inconsistent bead deposition, poor cutoff and improper bead placement due to mismatched or incorrect nozzle sizes are significant problems for hot melt equipment users. Determining the optimum nozzle orifice diameter, engagement length and nozzle angle requires time.

Unfortunately, these set-up parameters are often lost when replacement nozzles are installed.



Choose Saturn right-angle nozzles for low-profile guns.

Nordson's superior right-angle precision nozzles for low-profile packaging applications also use color-coded rings to identify the nozzle's orifice engagement and the angle of the nozzle tip. Right-angle nozzles are available in single-orifice and dual-orifice 15° or 30° styles.



Right-angle nozzles have been re-designed to improve durability:

- Entire nozzle assembly is made of brass, assuring heat transfer to the nozzle tip.
- A clamping nut securely holds the nozzle in position, even in the most demanding applications.
- Over tightening of the clamping nut will not harm the nozzle assembly.
- Internal o-ring seal has been eliminated, allowing the use of more aggressive cleaning methods and solvents.

Simplify nozzle replacement with Saturn Precision Nozzles.

Patented Saturn Precision Nozzles are available as direct replacements for the popular 237XXX series and right-angle nozzles used on Nordson automatic pneumatic and electric gun modules.

The color-coded Saturn ring system simplifies nozzle replacement because the two colored rings represent your nozzle's two key dimensions.

Single-Orifice Saturn Nozzles

The two colored rings of the standard single-orifice nozzles represent orifice diameter and orifice length (engagement).



Saturn Single-Orifice Precision Nozzles Part Number Color Chart




Orifice Diameter	Engagement Length				
	1.3 mm (0.050 in.) Purple	1.9 mm (0.075 in.) Brown	2.5 mm (0.100 in.) Blue	3.8 mm (0.150 in.) Green	7.6 mm (0.300 in.) Black
0.20 mm Purple (0.008 in.)	322008				
0.25 mm Blue (0.010 in.)	322010	322110			
0.30 mm Green (0.012 in.)	322012	322112	322212	322312	322412
0.36 mm Yellow (0.014 in.)	322014	322114	322214	322314	322414
0.41 mm Orange (0.016 in.)	322016	322116	322216	322316	322416
0.46 mm Red (0.018 in.)	322018	322118	322218	322318	322418
0.51 mm Beige (0.020 in.)	322020	322120	322220	322320	
0.53 mm Brown (0.021 in.)					322421
0.61 mm Gray (0.024 in.)	322024	322124	322224	322324	322424
0.71 mm Black (0.028 in.)					322428


Easy-to-use, peel-off labels shipped with each nozzle affix to the gluing station for quick reference. These labels indicate the color codes, part number and actual nozzle dimensions.

Right-Angle Saturn Nozzles

The two colored rings of the Saturn right-angle nozzle represent the angle of the nozzle tip and the orifice diameter.

Dual Bead 15°
1015812






SATURN
RIGHT ANGLE NOZZLE













www.nordson.com
13mm Hex

Patented


Saturn Right-Angle Precision Nozzles Part Number Color Chart



Orifice Diameter

0.20 mm Purple (0.008 in.)		1011008		
0.25 mm Blue (0.010 in.)		1011010		
0.30 mm Green (0.012 in.)		1011012	1015812	1015912
0.36 mm Yellow (0.014 in.)		1011014	1015814	1015914
0.41 mm Orange (0.016 in.)		1011016	1015816	1015916
0.46 mm Red (0.018 in.)		1011018	1015818	1015918
0.51 mm Beige (0.020 in.)		1011020	1015820	1015920
0.61 mm Gray (0.024 in.)		1011024	1015824	1015924
0.71 mm Black (0.028 in.)		1011028	1015828	1015928
0.81 mm Gold (0.032 in.)		1011032		
1.02 mm Turquoise (0.040 in.)		1011040		
Service Kit (screw and washer - 10 ea. per kit)		1027389	1027389	1027389

Nozzle Angle

Dual
15 Degree
Brown


Dual
30 Degree
Blue


NOTE:

- 7-digit Nordson part number
- 13 mm hex size
- Do not mix with old 6-digit part number nozzles

Precision nozzles keep adhesive application under control.

Nordson's family of precision nozzles includes standard nozzles for electric guns, pneumatic guns and handguns. All Nordson nozzles are manufactured and controlled to strict tolerances for inside diameter and engagement to maximize your control over adhesive deposition.

Specifications

Automatic gun nozzles

Nozzle	Orifice Diameter ³	Engagement ³
Saturn 322 XXX ¹	0.008 - 0.024 in. (0.20 - 0.61 mm)	0.050 - 0.150 in. (1.27 - 3.81 mm)
Saturn 322 4XX ¹	0.012 - 0.028 in. (0.30 - 0.71 mm)	0.300 in. only (7.62 mm)
Saturn Rt. Angle 101 XXXX	0.008 - 0.040 in. (0.20 - 1.02 mm)	0.075 in. inserts (1.9 mm)
238 OXX ¹	0.012 - 0.040 in. (0.30 - 1.02 mm)	0.100 in. only (2.54 mm)
238 XXX ²	0.008 - 0.030 in. (0.20 - 0.76 mm)	N/A
232 XXX ¹	0.008 - 0.024 in. (0.20 - 0.61 mm)	0.050 - 0.150 in. (1.27 - 3.81 mm)
220 XXX ²	0.008 - 0.020 in. (0.20 - 0.51 mm)	0.050 - 0.150 in. (1.27 - 3.81 mm)
236 XXX ¹	0.008 - 0.020 in. (0.20 - 0.51 mm)	0.050 - 0.150 in. (1.27 - 3.81 mm)
236 OXX ¹	0.016 - 0.028 in. (0.41 - 0.71 mm)	0.300 in. only (7.62 mm)



Single and multi-orifice gun nozzles provide high flow rates and clean cutoff.



Screw-in nozzles for guns and T-bar adapters deliver uniform patterns and consistent flow.

Handgun nozzles

Nozzle	Orifice Diameter ³	Engagement ³
238 Male ¹ threaded	0.020 - 0.156 in. (0.51 - 3.96 mm)	2.55 in. (64.77 mm)

1. Available in single-orifice nozzle.

2. Multi-orifice nozzle; requires retaining nut; steel and phosphor bronze designs available.

3. Orifice diameter and engagement significantly affect the nozzle's flow rating. Generally, the flow rate will increase exponentially with increasing orifice diameter and will decrease linearly with increasing engagement. Nordson recommends testing the flow rate using your material and equipment prior to large-scale nozzle changes. Optimal pressure range for positive cutoff is 400-700 psi.



For more information, talk with your Nordson representative or contact your Nordson regional office.

United States

Duluth, Georgia

Telephone: (800) 683-2314

Toll-free Facsimile:

(866) 667-3329

Canada

Markham, Ontario

Telephone: (800) 463-3200

Facsimile: (905) 475-8821

Europe

Lüneburg, Germany

Telephone: (49) 4131-894-0

Facsimile: (49) 4131-894-149

Japan

Tokyo, Japan

Telephone: (81) 3-5762-2700

Facsimile: (81) 3-5762-2701

Asia/Australia/

Latin America

Amherst, Ohio

Telephone: (440) 985-4797

Facsimile: (440) 985-1096

www.nordson.com



When you expect more.[®]

Nordson Corporation • 11475 Lakefield Drive • Duluth, Georgia 30097-1511